



EZ2200C PRO

The "All-Purpose" desktop thermal transfer printer for light to medium duty applications

GoDEX EZ2200C PRO is a Value-priced reliable desktop printer which is perfect for medium duty applications. With its highly stability and durability, EZ2200C PRO is still the best choice for most general applications.

EZ2200C PRO

Desktop Printer

| Model | | EZ2200C PRO |
|---------------|---------------------|--|
| Print Method | | Thermal Transfer/Direct Thermal |
| Resolution | | 203 dpi (8 dot/mm) |
| Print Speed | | 4 I PS (1.02 mm /s) |
| Print Width | | 4.25" (108 mm) |
| Memory | Flash | 4MB Flash (2 MB for user storage) |
| | SDRAM | 8MB SDRAM |
| Sensor Type | | Adjustable reflective sensor Fixed transmissive sensors, central aligned |
| Media | Types | Continuous form, gap labels, black mark sensing and punched hole; label length set by auto sensing or programming. |
| | Width | 1" (25.4 mm) Min. - 4.64" (118 mm) Max. |
| | Thickness | 0.003" (0.06 mm) Min. - 0.01" (0.25 mm) Max. |
| | Label Roll Diameter | Max. 5" (127 mm) |
| Core Diameter | | 1", 1.5", 3" (25.4 mm, 38.1 mm, 76.2 mm) |

| | | |
|---------------------------------|------------------------------|---|
| Ribbon | Types | Wax, wax / resin, resin |
| | Width | 981' (300 m) |
| | Thickness | 1.18" Min. – 4.33" (30 mm - 110 mm) Max. |
| | Ribbon Roll Diameter | 2.67" (68 mm) |
| | Core Diameter | 1" (25.4 mm) |
| Printer Language | | EZ PL, GEPL (Godex Eltron® Printer Language), GZPL (Godex Zebra® Printer Language) |
| Software | Label Design Software | QLabel-IV (for EZPL only) |
| | Driver | Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1 |
| | Dell | Win CE , .NET , Windows Mobile, Windows 2000 / XP / VISTA / Windows 7 / Windows 8.1 / Android |
| Resident Fonts | Bitmap | 6, 8, 10, 12, 14, 18, 24, 30, 16X 26 and OCRA&B Bitmap fonts 90°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable Bitmap fonts 8 times expandable in horizontal and vertical direction |
| | TTF Fonts | CG Triumvirate MT (Bold / Italic / Underline) 90°, 180°, 270° rotatable |
| Download Fonts | Bitmap Fonts | 9 0°, 180°, 270° rotatable, single characters 90°, 180°, 270° rotatable |
| | Asian Fonts | 16x16, 24x24. Traditional Chinese (BIG-5), Simplified Chinese(GB2312), Japanese (S-JIS), Korean (KS-X1001) 90°, 180°, 270° rotatable and 8 times expendable in horizontal and vertical direction |
| | TTF Fonts | 90°, 180°, 270° rotatable |
| Barcodes | 1-D Bar Codes | Code 39, Code 93, Code 128 (subset A, B, C), UCC/EAN-128 K-Mart, UCC/EAN-128, UPC A / E (add on 2 & 5), I 2 of 5, I 2 of 5 with Shipping Bearer Bars, EAN 8 / 13 (add on 2 & 5), Codabar, Post NET, EAN 128, DUN 14, HIBC, MSI (1 Mod 10), Random Weight, Telepen, FIM, China Postal Code, RPS 128 and GS1 DataBar |
| | 2-D Bar Codes | PDF4 1 7 , Data matrix code, Maxi Code, QR code and Micro QR code |
| Code Pages | | Codepage 437, 850, 851, 852, 855, 857, 860, 861, 862, 863, 865, 866, 869, 737 Windows 1250, 1251, 1252, 1253, 1254, 1255 Unicode UTF8, UTF16BE , UTF16LE |
| Graphics | | Resident graphic file types are BMP and PCX, other graphic formats are downloadable from the software |
| Interfaces | | Serial port: RS-232 (DB-9) USB port (default on) Parallel port: Centronics 36-pin |
| Control Panel | | Two bi-color status-LEDs: Ready & Status Control key: FEED |
| Power | | Auto Switching 100-240VAC, 50-60Hz |
| Environment | Operation Temperature | 41°F to 104°F (5°C to 40°C) |
| | Storage Temperature | -4°F to 122°F (-20°C to 50°C) |
| Humidity | Operation | 30-85%, non-condensing |
| | Storage | 10-90%, non-condensing |
| Agency Approvals | | CE(E MC) , FCC Class A, CB, cU L, CCC |
| Dimension | Length | 11.2" (285 mm) |
| | Height | 6.8" (171 mm) |
| | Width | 8.9" (226 mm) |
| Cutter | | Yes/ automatic |
| Weight | | 6 lbs (2.72 Kg), excluding consumables |
| Options& Accessories | | Label Dispenser External label roll holder for 10" (250 mm) O.D. label rolls External label rewinder CF card adapter with real time clock (max. 1GB CF card) Ethernet 10/100Mbps print server (default off; disable USB when in use) 802.11 b/g wireless print server (Default off; disables USB when in use. Must remove PS2 port and Ethernet card to install) |